

(19) World Intellectual Property  
Organization  
International Bureau



(43) International Publication Date  
12 May 2005 (12.05.2005)

PCT

(10) International Publication Number  
**WO 2005/043771 A1**

(51) International Patent Classification<sup>7</sup>: **H04B 3/00**,  
H04R 3/00, H03G 5/00

(21) International Application Number:  
PCT/US2004/034922

(22) International Filing Date: 21 October 2004 (21.10.2004)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:  
60/513,804 23 October 2003 (23.10.2003) US

(71) Applicant (for all designated States except US): **AMERICAN TECHNOLOGY CORPORATION [US/US]**;  
13114 Evening Creek Drive South, San Diego, CA 92128 (US).

(72) Inventor; and

(75) Inventor/Applicant (for US only): **CROFT, James, J., III [US/US]**; 13633 Quiet Hills Drive, Poway, CA 92064 (US).


(74) Agents: **NORTH, Vaughn, W. et al.**; Thorpe, North & Western, LLP, P.O. Box 1219, Sandy, UT 84091-1219 (US).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI,

[Continued on next page]

(54) Title: METHOD OF ADJUSTING LINEAR PARAMETERS OF A PARAMETRIC ULTRASONIC SIGNAL TO REDUCE NON-LINEARITIES IN DECOUPLED AUDIO OUTPUT WAVES AND SYSTEM INCLUDING SAME



(57) Abstract: A method and system of producing a parametric ultrasonic wave (148) to be decoupled in air to create a decoupled audio wave that closely corresponds to an audio input signal (131). The method is comprised of ascertaining (402) a linear response over a predefined frequency range of an acoustic output of an electro-acoustical emitter (146) to be used for parametric ultrasonic output. A parametric ultrasonic processed signal (144) is then created by adjusting (404) linear parameters of at least one sideband frequency range of a parametric ultrasonic signal to compensate for the linear response of the acoustic output of the electro-acoustical emitter (146) such that when the parametric ultrasonic wave is propagated, having sidebands that are closely matched at least at a predefined point in space over the at least one sideband frequency range.



SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

*For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*

**Published:**

- *with international search report*
- *before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments*